

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)

Form Approved
OMB No. 1218-0072

HMIS H-1, F-0-R-0



IDENTITY (As Used on Label and List)

LEATHER SIZE

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

| | |
|--|--|
| Manufacturer's Name Royaltone Co. Inc. | Emergency Telephone Number 918-663-9666 |
| Address (Number, Street, City, State, and ZIP Code) 9504 E 55th St. Tulsa OK 74145 | Telephone Number for Information 918-622-6677 |
| | Date Prepared 5/29/07 |
| | Signature of Preparer (optional) |

Section II — Hazardous Ingredients/Identity Information

| Hazardous Components (Specific Chemical Identity; Common Name(s)) | OSHA PEL | ACGIH TLV | Other Limits Recommended | % (optional) |
|---|----------|-----------|--------------------------|--------------|
|---|----------|-----------|--------------------------|--------------|

This product does not contain any hazardous materials based on current Department of Labor regulations. This material has not been listed under Subpart H (Hazardous Material) Or Subpart Z (Toxic substances) of Part 1910 Occupational Safety and Health Standard of the OSHA, Fed. Reg. 20 CFR-1910

Section III — Physical/Chemical Characteristics

| | | | |
|-------------------------|-----------------------------------|---|-------|
| Boiling Point | 212°F | Specific Gravity (H ₂ O = 1) | 1.152 |
| Vapor Pressure (mm Hg.) | 17 | Melting Point | 60 |
| Vapor Density (AIR = 1) | 0.62 | Evaporation Rate (Butyl Acetate = 1) | -1 |
| Solubility in Water | 100% Storage life @ 70°F 3 months | | |
| Appearance and Odor | creme color with mild odor | | |

Section IV — Fire and Explosion Hazard Data

| | | | | |
|------------------------------------|---|------------------|-----|-----|
| Flash Point (Method Used) | none | Flammable Limits | LEL | UEL |
| Extinguishing Media | water, chemical foam, carbon dioxide | | | |
| Special Fire Fighting Procedures | water or water spray may be used to cool closed containers to minimize pressure build up during fire. | | | |
| Unusual Fire and Explosion Hazards | will not burn unless liquid has evaporated | | | |

