

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory-Form)

Form Approved

OMB No. 1218-0072

IDENTITY (As Used on Label and List) Leather soft	<i>Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.</i>
---	--

Section I – Identity		NA = Not Applicable NIA = No Information Available			
Manufacturer's Name ROYALTONE CO, INC.	Emergency Telephone Number 918-663-9666				
Address (Number, Street, City, State, and ZIP Code) 9504 E. 55 TH ST, TULSA OK 74145	Telephone Number For Information 918-622-6677				
	Date Prepared				
Chemical Family	Signature of Preparer (optional)				

Section II – Hazardous Ingredients					
Chemical Identity; Common Name(s)	CAS #	OSHA PEL	ACGIH TLV	Other Limits	%(optional)
NONE					

Section III – Physical Data			
Boiling Point	625 F	Specific Gravity (H ₂ O=1)	0.87
Vapor Pressure (mm Hg.)	0.0001	Melting Point	1.0
Vapor Density (AIR=1)	10	Evaporation Rate (Butyl Acetate = 1)	Na
pH ,1%	NA	% Volatile	NA
Solubility In Water Form emulsion			
Appearance and Odor Light amber liquid with little odor			

Section IV – Fire and Explosion Hazard Data			
Flash Point (Method Used) 380 COC	Flammable Limits	LEL NA	UEL NA
Extinguishing Media FOAM, DRY CHEMICAL, CO2, WATER FOG			
Special Fire Fighting Procedures WEAR SELF CONTAINED BREATHING APPARATUS			
Unusual Fire and Explosion Hazards ESTIMATED AUTO IGNITION TEMPERATURE 670 F CAN BE MADE TO BURN (FLASH POINT GREATER THAN 200 F)			

Section V – Physical Hazards / Reactivity Data

Stability	Unstable		Conditions to avoid
	Stable	X	Contact with strong oxidizers

Incompatibility (*Materials to Avoid*)

STRONG OXIDIZING

Hazardous Decomposition or Byproducts

Carbon monoxides and asphyxiates

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NONE

Section VI – Health Hazard Data

Routes(s) of Entry:	Inhalation?	Skin?	Ingestion?
	X	X	YES

Health Hazards (*Acute and Chronic*)

Eye contact may cause irritation and discomfort. Skin contact might cause slight irritation. Ingestion causes diarrhea

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
NO	NO	NO	NO

Signs and Symptoms of Exposure

Na

Medical Conditions Generally Aggravated by Exposure

NA

Section VII – First Aid Measures

1. Inhalation

NA

2. Eyes

Flush with large amounts of water for at least 15 minutes, get immediate medical attention

3. Skin

Wash skin with soap and water, remove and wash clothing before reuse

4. Ingestion

See a physician, induce vomiting if conscious

Section VIII – Preventative MeasuresRespiratory Protection (*Specify Type*)

None

Ventilation	Local Exhaust Adequate	Special NONE REQUIRED
	Mechanical (<i>General</i>) NONE REQUIRED	Other NONE REQUIRED

Protective Gloves	Eye Protection
Na	Na

Other Protective Clothing or Equipment

Na

Work/Hygienic Practices

Do not ingest. Keep out of eyes and off of skin

Section IX – Special Precautions / Spill Leak Procedures

Steps to Be Taken in Case Material is Released or Spilled

Wash with water containing detergent or absorb with clay, Diatomaceous earth or other inert absorbent.

Waste Disposal Method

DISPOSE OF IN ACCORDANCE TO LOCAL, STATE AND FEDERAL REGULATIONS

Precautions to Be Taking in Handling and Storing

Drum and dump or incinerate as governed by federal, state and local regulations, or chemical waste

Other Precautions

Do not swallow

Section X– Other Information