



Spot Wiz Dry

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 05/26/2015 Version: 2.0

SECTION 1: Product and Company Identification

1.1. Product identifier

Product name : Spot Wiz Dry

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Dry cleaning fluids and detergents

1.3. Details of the supplier of the safety data sheet

ROYALTONE, Inc.
7211 N. Harrison Ave.
Shawnee, OK 74804 - USA
T 1-405-878-0537
Royaltone@royaltone.com

1.4. Emergency telephone number

Emergency number : 1-405-878-0577

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS)

Skin Irrit. 2 H315
Eye Irrit. 2B H320
Muta. 2 H341
Carc. 1B H350
STOT SE 3 H336

Full text of H-phrases: see section 16

2.2. Label elements

GHS labeling

Hazard pictograms (GHS) :



GHS07

GHS08

Signal word (GHS) :

Danger

Hazard statements (GHS) :

H315 - Causes skin irritation
H320 - Causes eye irritation
H336 - May cause drowsiness or dizziness
H341 - Suspected of causing genetic defects
H350 - May cause cancer

Precautionary statements (GHS) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P261 - Avoid breathing mist, vapors
P264 - Wash hands thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear eye protection, protective gloves, Approved respirator, protective clothing
P302+P352 - If on skin: Wash with plenty of soap, water
P332+P313 - If skin irritation occurs: Get medical advice/attention
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P312 - Call a doctor if you feel unwell
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337+P313 - If eye irritation persists: Get medical advice/attention
P308+P313 - If exposed or concerned: Get medical advice/attention
Treat symptomatically
P362 - Take off contaminated clothing and wash before reuse
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up
P501 - Dispose of contents/container to an approved waste disposal plant

Spot Wiz Dry

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

| Component | CAS (Chemical Abstracts Service) number | % | Classification (GHS) |
|-------------------------------------|---|---------|--|
| Trichloroethylene | 79-01-6 | 55 - 60 | Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Muta. 2, H341 Carc. 1B, H350 STOT SE 3, H336 |
| Hydrocarbon solvent* | | 30 - 35 | Flam. Liq. 3, H226 Asp. Tox. 1, H304 |
| Proprietary paraffinic oil (heavy)* | | 5 - 10 | Asp. Tox. 1, H304 |
| Proprietary paraffinic oil (light)* | | 1 - 5 | Asp. Tox. 1, H304 |

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|---|
| First-aid measures general | : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). |
| First-aid measures after inhalation | : Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell. |
| First-aid measures after skin contact | : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. |
| First-aid measures after eye contact | : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| First-aid measures after ingestion | : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|--------------------------------------|--------------------------------------|
| Symptoms/injuries after inhalation | : May cause drowsiness or dizziness. |
| Symptoms/injuries after skin contact | : Causes skin irritation. |
| Symptoms/injuries after eye contact | : Causes eye irritation. |

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|--------------------------------|--|
| Suitable extinguishing media | : Foam. Dry powder. Carbon dioxide. Water spray. Sand. |
| Unsuitable extinguishing media | : Do not use a heavy water stream. |

5.2. Special hazards arising from the substance or mixture

| | |
|-------------|--|
| Fire hazard | : Heat from fire may generate flammable vapor. |
| Reactivity | : Stable : Not reactive when mixed with water. |

5.3. Advice for firefighters

| | |
|--------------------------------|---|
| Firefighting instructions | : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. |
| Protection during firefighting | : Do not enter fire area without proper protective equipment, including respiratory protection. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

| | |
|----------------------|-----------------------------------|
| Emergency procedures | : Evacuate unnecessary personnel. |
|----------------------|-----------------------------------|

6.1.2. For emergency responders

| | |
|----------------------|--|
| Protective equipment | : Equip cleanup crew with proper protection. Avoid breathing Vapors. |
| Emergency procedures | : Ventilate area. |

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Spot Wiz Dry

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Heating increases the fire hazard.
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Obtain special instructions before use. Use personal protective equipment as required. Do not handle until all safety precautions have been read and understood. Avoid breathing mist, vapors. Use only outdoors or in a well-ventilated area.
Hygiene measures : Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Sources of ignition. Keep container tightly closed.
Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight.
Storage temperature : 0 - 30 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Spot Wiz Dry | | |
|------------------------------------|--------------------------------|--|
| ACGIH | Not applicable | |
| OSHA | Not applicable | |
| Hydrocarbon solvent | | |
| ACGIH | Not applicable | |
| OSHA | Not applicable | |
| Proprietary paraffinic oil (heavy) | | |
| ACGIH | ACGIH TWA (mg/m ³) | 5 mg/m ³ Oil mist, mineral (inhalable fraction) |
| OSHA | Not applicable | |
| Proprietary paraffinic oil (light) | | |
| ACGIH | ACGIH TWA (mg/m ³) | 5 mg/m ³ Oil mist, mineral (inhalable fraction) |
| OSHA | Not applicable | |
| Trichloroethylene (79-01-6) | | |
| ACGIH | ACGIH TWA (ppm) | 10 ppm |
| ACGIH | ACGIH STEL (ppm) | 25 ppm |
| ACGIH | Remark (ACGIH) | CNS impair; cognitive decrements |
| OSHA | Remark (OSHA) | (2) See Table Z-2. |

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Personal protective equipment : Avoid all unnecessary exposure.
Hand protection : Wear protective gloves.
Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable protective clothing.
Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
Other information : Do not eat, drink or smoke during use.

Spot Wiz Dry

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---|
| Physical state | : Liquid |
| Color | : Colorless to Slightly Amber |
| Odor | : Characteristic |
| Odor threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Relative evaporation rate (ether=1) | : < 1 |
| Melting point | : No data available |
| Freezing point | : < -15 °C |
| Boiling point | : > 87 °C |
| Flash point | : > 94 °C |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapor pressure | : < 61 mm Hg @ 20 °C |
| Relative vapor density at 20 °C | : > 1 (air = 1.0) |
| Relative density | : 1.09 |
| Specific gravity / density | : ≈ 1.1 g/ml @ 25 °C |
| Solubility | : Insoluble in water. |
| Log Pow | : No data available |
| Log Kow | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive properties | : Heating may cause the release of flammable vapors |
| Oxidizing properties | : No data available |
| Explosive limits | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable : Not reactive when mixed with water.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None under normal use.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Fumes. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| | |
|----------------------------|--------------------|
| Hydrocarbon solvent | |
| LD50 oral rat | > 2000 mg/kg (Rat) |

Spot Wiz Dry

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---|----------------------------|
| Proprietary paraffinic oil (heavy) | |
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rabbit | > 5000 mg/kg |
| Proprietary paraffinic oil (light) | |
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rabbit | > 5000 mg/kg |
| Trichloroethylene (79-01-6) | |
| LD50 oral rat | 4920 mg/kg (Rat) |
| LD50 dermal rabbit | > 20000 mg/kg (Rabbit) |
| LC50 inhalation rat (mg/l) | 66 mg/l/4h (Rat) |
| LC50 inhalation rat (ppm) | 12000 ppm/4h (Rat) |
| ATE US (oral) | 4920.000 mg/kg body weight |
| ATE US (gases) | 12000.000 ppmV/4h |
| ATE US (vapors) | 66.000 mg/l/4h |
| ATE US (dust, mist) | 66.000 mg/l/4h |

| | |
|-----------------------------------|---|
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Causes eye irritation. |
| Respiratory or skin sensitization | : Not classified |
| Germ cell mutagenicity | : Suspected of causing genetic defects. |
| Carcinogenicity | : May cause cancer. |

| | |
|--|---|
| Trichloroethylene (79-01-6) | |
| IARC group | 2A - Probably carcinogenic to humans |
| National Toxicology Program (NTP) Status | 3 - Reasonably anticipated to be Human Carcinogen |

| | |
|--|--------------------------------------|
| Reproductive toxicity | : Not classified |
| Specific target organ toxicity (single exposure) | : May cause drowsiness or dizziness. |

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation : May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

| | |
|---|---|
| Proprietary paraffinic oil (heavy) | |
| LC50 fish 1 | > 100 mg/l |
| EC50 Daphnia 1 | > 100 mg/l |
| ErC50 (algae) | > 100 mg/l |
| NOEC chronic fish | > 100 mg/l |
| Proprietary paraffinic oil (light) | |
| LC50 fish 1 | > 100 mg/l |
| Trichloroethylene (79-01-6) | |
| LC50 fish 1 | 40.7 mg/l (96 h; Pimephales promelas) |
| LC50 other aquatic organisms 1 | 20 mg/l (48 h; Plankton) |
| EC50 Daphnia 1 | 39 - 51 mg/l (48 h; Daphnia pulex; Static system) |
| LC50 fish 2 | 45 mg/l (96 h; Lepomis macrochirus) |
| EC50 Daphnia 2 | 20.8 mg/l (48 h; Daphnia magna) |
| TLM fish 1 | 100 - 1000,96 h; Pisces |
| TLM other aquatic organisms 1 | 100 - 1000,96 h |
| Threshold limit other aquatic organisms 1 | 20 mg/l (48 h; Plankton) |
| Threshold limit algae 1 | > 100 mg/l (Scenedesmus quadricauda) |
| Threshold limit algae 2 | 63 mg/l (Microcystis aeruginosa) |

Spot Wiz Dry

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

| | |
|------------------------------------|---|
| Spot Wiz Dry | |
| Persistence and degradability | Not established. |
| Hydrocarbon solvent | |
| Persistence and degradability | Biodegradability in water: no data available. |
| Trichloroethylene (79-01-6) | |
| Persistence and degradability | Not readily biodegradable in water. Non degradable in the soil. Biodegradable in the soil under anaerobic conditions. |

12.3. Bioaccumulative potential

| | |
|---|--|
| Spot Wiz Dry | |
| Bioaccumulative potential | Not established. |
| Hydrocarbon solvent | |
| Bioaccumulative potential | No bioaccumulation data available. |
| Proprietary paraffinic oil (heavy) | |
| Log Pow | > 6 |
| Proprietary paraffinic oil (light) | |
| Log Pow | > 6 |
| Trichloroethylene (79-01-6) | |
| BCF fish 1 | 17 (336 h; Lepomis macrochirus) |
| BCF fish 2 | 90 (72 h; Leuciscus idus; Fresh water) |
| BCF other aquatic organisms 1 | 3440 (120 h; Selenastrum capricornutum) |
| BCF other aquatic organisms 2 | 4270 (120 h; Scenedesmus quadricauda) |
| Log Pow | 2.29 - 2.42 (Experimental value) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |

12.4. Mobility in soil

| | |
|------------------------------------|----------|
| Trichloroethylene (79-01-6) | |
| Surface tension | 0.03 N/m |

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to an approved waste disposal plant.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with US Dept. of Transportation (DOT)

Transport document description : UN1710 Trichloroethylene solution, 6.1, III

UN-No.(DOT) : UN1710

Proper Shipping Name (DOT) : Trichloroethylene solution

Department of Transportation (DOT) Hazard Classes : 6.1 - Class 6.1 - Poisonous materials 49 CFR 173.132

Hazard labels (DOT) : 6.1 - Poison inhalation hazard



Packing group (DOT) : III - Minor Danger

Spot Wiz Dry


Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
 N36 - Aluminum or aluminum alloy construction materials are permitted only for halogenated hydrocarbons that will not react with aluminum.
 T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
 TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 153
 DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
 DOT Packaging Bulk (49 CFR 173.xxx) : 241
 DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L
 DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L
 DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
 DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Additional information

- Other information : Limited Quantity Shipping:
 When shipped by ground transport in inner packagings not over 4.0 L (1 gallon) net capacity, this product may be shipped under the US Dept. of Transportation (DOT) 'Limited Quantity Exception' per 49CFR§172.315.
 Hazard label (DOT): LTD QTY - Limited quantity



SECTION 15: Regulatory information

15.1. US Federal regulations

| | |
|-------------------------------------|--|
| Spot Wiz Dry | |
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard Immediate (acute) health hazard |

All components of this product are listed on the Toxic Substances Control Act (TSCA) inventory

| | |
|--|--------|
| Trichloroethylene (79-01-6) | |
| Listed on United States SARA Section 313 | |
| RQ (Reportable quantity, section 304 of EPA's List of Lists) | 100 lb |

15.3. US State regulations

| | | | | |
|--|---|---|---|-----------------------------------|
| Trichloroethylene (79-01-6) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| Yes | No | No | No | 14 |
| Trichloroethylene (79-01-6) | | | | |
| U.S. - New Jersey - Right to Know Hazardous Substance List | | | | |
| U.S. - Pennsylvania - RTK (Right to Know) List | | | | |

SECTION 16: Other information

Spot Wiz Dry

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

| | |
|---------------|---|
| Asp. Tox. 1 | Aspiration hazard Category 1 |
| Carc. 1B | Carcinogenicity Category 1B |
| Eye Irrit. 2B | Serious eye damage/eye irritation Category 2B |
| Flam. Liq. 3 | Flammable liquids Category 3 |
| Muta. 2 | Germ cell mutagenicity Category 2 |
| Skin Irrit. 2 | Skin corrosion/irritation Category 2 |
| STOT SE 3 | Specific target organ toxicity (single exposure) Category 3 |
| H226 | Flammable liquid and vapor |
| H304 | May be fatal if swallowed and enters airways |
| H315 | Causes skin irritation |
| H320 | Causes eye irritation |
| H336 | May cause drowsiness or dizziness |
| H341 | Suspected of causing genetic defects |
| H350 | May cause cancer |

HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur
Flammability : 1 Slight Hazard
Physical : 0 Minimal Hazard
Personal protection : H

Royaltone SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product